CRC

SAFETY DATA SHEET

1. Identification

Product identifier 2-26® Multi-Purpose Precision Lubricant

Other means of identification

Product code 02007

Recommended use Multi-purpose lubricant

Recommended restrictions None known.

Manufacturer/Importer/Supplier/Distributor information

Manufactured or sold by:

Company name CRC Industries, Inc.

Address 885 Louis Dr.

Warminster, PA 18974 US

Telephone

 General Information
 215-674-4300

 Technical
 800-521-3168

Assistance

Customer Service 800-272-4620 **24-Hour Emergency** 800-424-9300 (US)

(CHEMTREC) 703-527-3887 (International)
Website www.crcindustries.com

2. Hazard(s) identification

Physical hazards Not classified.

Health hazardsAspiration hazardCategory 1Environmental hazardsHazardous to the aquatic environment, acuteCategory 2

hazard

OSHA defined hazards Not classified.

Label elements



Signal word Danger

Hazard statement May be fatal if swallowed and enters airways. Toxic to aquatic life.

Precautionary statement

Prevention Use with adequate ventilation. Open doors and windows or use other means to ensure a fresh air

supply during use and while product is drying. If you experience any symptoms listed on this label,

increase ventilation or leave the area. Avoid release to the environment.

Response If swallowed: Immediately call a poison center/doctor. Do NOT induce vomiting.

Storage Store locked up

Disposal Dispose of contents/container in accordance with local/regional/national regulations.

Hazard(s) not otherwise

classified (HNOC)

None known.

3. Composition/information on ingredients

Mixtures

| Chemical name | Common name and synonyms | CAS number | % |
|---|--------------------------|------------|---------|
| Distillates (petroleum), hydrotreated light | | 64742-47-8 | 70 - 80 |

Material name: 2-26® Multi-Purpose Precision Lubricant
02007 Version #: 03 Revision date: 01-07-2016 Issue date: 01-07-2016

| Chemical name | Common name and synonyms | CAS number | % | |
|--------------------------------|--------------------------|------------|---------|--|
| Light mineral oil | | 8042-47-5 | 10 - 20 | |
| n-Butyl stearate | | 123-95-5 | 3 - 5 | |
| Fatty Acids, C18-unsatd., Dime | ers | 61788-89-4 | 1 - 3 | |
| Petrolatum | | 8009-03-8 | 1 - 3 | |

Specific chemical identity and/or percentage of composition has been withheld as a trade secret.

protect themselves.

4. First-aid measures

| Inhalation | Remove victim to fresh air and keep at rest in a position comfortable for breathing. Call a POISON CENTER or doctor/physician if you feel unwell. |
|--|---|
| Skin contact | Rinse skin with water/shower. Take off contaminated clothing and wash before reuse. If skin irritation occurs: Get medical advice/attention. |
| Eye contact | Rinse with water. Get medical attention if irritation develops and persists. |
| Ingestion | Call a physician or poison control center immediately. Rinse mouth. Do not induce vomiting. Aspiration may cause pulmonary edema and pneumonitis. If vomiting occurs, keep head low so that stomach content doesn't get into the lungs. |
| Most important symptoms/effects, acute and delayed | Aspiration may cause pulmonary edema and pneumonitis. |
| Indication of immediate medical attention and special treatment needed | Provide general supportive measures and treat symptomatically. Keep victim under observation. Symptoms may be delayed. |

Ensure that medical personnel are aware of the material(s) involved, and take precautions to

5. Fire-fighting measures

General information

| Suitable extinguishing media | Alcohol resistant foam. Powder. Dry chemicals. Carbon dioxide (CO2). |
|---|--|
| Unsuitable extinguishing media | Do not use water jet as an extinguisher, as this will spread the fire. |
| Specific hazards arising from the chemical | During fire, gases hazardous to health may be formed. |
| Special protective equipment and precautions for firefighters | Self-contained breathing apparatus and full protective clothing must be worn in case of fire. |
| Fire-fighting equipment/instructions | Cool containers exposed to heat with water spray and remove container, if no risk is involved. |
| General fire hazards | No unusual fire or explosion hazards noted. |

| equipment/instructions | Cool containers exposed to neat with water spray and remove container, it no risk is involved. | | |
|---|--|--|--|
| General fire hazards | No unusual fire or explosion hazards noted. | | |
| 6. Accidental release mea | asures | | |
| Personal precautions, protective equipment and emergency procedures | Keep unnecessary personnel away. Wear appropriate protective equipment and clothing during clean-up. Ensure adequate ventilation. Local authorities should be advised if significant spillages cannot be contained. For personal protection, see section 8 of the SDS. | | |
| Methods and materials for containment and cleaning up | Use water spray to reduce vapors or divert vapor cloud drift. This product is miscible in water. Prevent product from entering drains. | | |
| | Large Spills: Stop the flow of material, if this is without risk. Dike the spilled material, where this is possible. Cover with plastic sheet to prevent spreading. Absorb in vermiculite, dry sand or earth and place into containers. Following product recovery, flush area with water. | | |
| | Small Spills: Wipe up with absorbent material (e.g. cloth, fleece). Clean surface thoroughly to remove residual contamination. | | |
| | Never return spills to original containers for re-use. For waste disposal, see section 13 of the SDS. | | |
| Environmental precautions | Avoid release to the environment. Inform appropriate managerial or supervisory personnel of all environmental releases. Prevent further leakage or spillage if safe to do so. Avoid discharge into drains, water courses or onto the ground. | | |

7. Handling and storage

Precautions for safe handling

Avoid prolonged or repeated contact with skin. Use only in well-ventilated areas. Wear appropriate personal protective equipment. Wash hands thoroughly after handling. Avoid release to the environment. Observe good industrial hygiene practices. For product usage instructions, please see the product label.

Conditions for safe storage, including any incompatibilities

Keep away from heat and sources of ignition. Store in a cool, dry place out of direct sunlight. Store away from incompatible materials (see Section 10 of the SDS).

8. Exposure controls/personal protection

| TWA r Air Contaminants (29 CFR 1910.1000) Type PEL | 5 mg/m3 Value | Respirable |
|--|---|---|
| Туре | Value | |
| | Value | |
| PEL | | Form |
| | 5 mg/m3 | Mist. |
| PEL | 5 mg/m3 | Mist. |
| | | |
| Туре | Value | Form |
| STEL | 10 mg/m3 | Respirable |
| TWA | 5 mg/m3 | Respirable |
| alues | | _ |
| Туре | Value | Form |
| TWA | 5 mg/m3 | Inhalable fraction. |
| TWA | 10 mg/m3 | |
| TWA | 5 mg/m3 | Inhalable fraction. |
| Chemical Hazards | | |
| Туре | Value | Form |
| TWA | 100 mg/m3 | |
| STEL | 10 mg/m3 | Mist. |
| TWA | 5 mg/m3 | Mist. |
| STEL | 10 mg/m3 | Mist. |
| TWA | 5 mg/m3 | Mist. |
| No biological exposure limits noted for the ing | redient(s). | |
| | Type STEL TWA alues Type TWA TWA TWA TWA TWA Shemical Hazards Type TWA STEL TWA Sood general ventilation (typically 10 air chan should be matched to conditions. If applicable | Type Value STEL 10 mg/m3 TWA 5 mg/m3 Alues Type Value TWA 5 mg/m3 TWA 10 mg/m3 TWA 5 mg/m3 TWA 5 mg/m3 TWA 5 mg/m3 TWA 5 mg/m3 Shemical Hazards Type Value TWA 100 mg/m3 STEL 10 mg/m3 TWA 5 mg/m3 STEL 10 mg/m3 |

or other engineering controls to maintain airborne levels below recommended exposure limits. If exposure limits have not been established, maintain airborne levels to an acceptable level.

Individual protection measures, such as personal protective equipment

Eye/face protection Wear safety glasses with side shields (or goggles).

Skin protection

Wear protective gloves such as: Nitrile. Neoprene. Hand protection

Other Wear suitable protective clothing.

Respiratory protection If engineering controls are not feasible or if exposure exceeds the applicable exposure limits, use a

NIOSH-approved cartridge respirator with an organic vapor cartridge. Use a self-contained breathing apparatus in confined spaces and for emergencies. Air monitoring is needed to

determine actual employee exposure levels.

Thermal hazards Wear appropriate thermal protective clothing, when necessary.

General hygiene considerations

Always observe good personal hygiene measures, such as washing after handling the material and before eating, drinking, and/or smoking. Routinely wash work clothing and protective

equipment to remove contaminants.

9. Physical and chemical properties

Appearance

Physical state Liquid. **Form** Liquid. Color Amber.

Odor Mild petroleum. **Odor threshold** Not available. Not available.

-56.2 °F (-49 °C) estimated Melting point/freezing point

Initial boiling point and boiling

range

Not available.

200 °F (93.3 °C) Tag Closed Cup Flash point

Evaporation rate Slow.

Not available. Flammability (solid, gas) Upper/lower flammability or explosive limits

Flammability limit - lower

0.6 % estimated

Flammability limit - upper

(%)

5.5 % estimated

0.6 hPa estimated Vapor pressure Vapor density > 1 (air = 1)0.82 Relative density Solubility (water) Negligible.

Partition coefficient

Not available.

(n-octanol/water)

Auto-ignition temperature 392 °F (200 °C) estimated

Decomposition temperature Not available. Viscosity (kinematic) Not available. 90.9 % estimated Percent volatile

10. Stability and reactivity

The product is stable and non-reactive under normal conditions of use, storage and transport. Reactivity

Chemical stability Material is stable under normal conditions.

Possibility of hazardous

reactions

No dangerous reaction known under conditions of normal use.

Avoid temperatures exceeding the flash point. Contact with incompatible materials. Conditions to avoid

Strong oxidizing agents. Incompatible materials

Hazardous decomposition

products

Carbon oxides.

11. Toxicological information

Information on likely routes of exposure

Inhalation Prolonged inhalation may be harmful.

Skin contact Prolonged skin contact may cause temporary irritation. Eye contact Direct contact with eyes may cause temporary irritation.

Ingestion Droplets of the product aspirated into the lungs through ingestion or vomiting may cause a serious

chemical pneumonia.

Material name: 2-26® Multi-Purpose Precision Lubricant

Symptoms related to the physical, chemical and toxicological characteristics Aspiration may cause pulmonary edema and pneumonitis. Headache. Nausea, vomiting.

Diarrhea.

Information on toxicological effects

May be fatal if swallowed and enters airways. Acute toxicity

Product Species Test Results

2-26® Multi-Purpose Precision Lubricant

Acute Dermal

LD50 Rabbit 2408 mg/kg estimated

Inhalation

LC50 Rat 57142 ppm, 4 hours estimated

Oral

LD50 Rat 6093 mg/kg estimated

* Estimates for product may be based on additional component data not shown

Skin corrosion/irritation Prolonged skin contact may cause temporary irritation. Serious eye damage/eye Direct contact with eyes may cause temporary irritation.

irritation

Respiratory sensitization Not a respiratory sensitizer.

Skin sensitization This product is not expected to cause skin sensitization.

Germ cell mutagenicity No data available to indicate product or any components present at greater than 0.1% are

mutagenic or genotoxic.

This product is not considered to be a carcinogen by IARC, ACGIH, NTP, or OSHA. Carcinogenicity

IARC Monographs. Overall Evaluation of Carcinogenicity

Light mineral oil (CAS 8042-47-5) 3 Not classifiable as to carcinogenicity to humans.

US. National Toxicology Program (NTP) Report on Carcinogens

Not available.

Reproductive toxicity This product is not expected to cause reproductive or developmental effects.

Specific target organ toxicity -

single exposure

Not classified.

Specific target organ toxicity -

repeated exposure

Not classified.

May be fatal if swallowed and enters airways. If aspirated into lungs during swallowing or vomiting, **Aspiration hazard**

may cause chemical pneumonia, pulmonary injury or death.

12. Ecological information

Ecotoxicity Toxic to aquatic life.

Species Test Results Components

Distillates (petroleum), hydrotreated light (CAS 64742-47-8)

Aquatic

Acute

LC50 Fish Bluegill (Lepomis macrochirus) 2.2 mg/l, 96 hours

* Estimates for product may be based on additional component data not shown.

No data is available on the degradability of this product. Persistence and degradability

Bioaccumulative potential

Partition coefficient n-octanol / water (log Kow)

Fatty Acids, C18-unsatd., Dimers 1 - 2.5, logKow

Mobility in soil No data available.

Other adverse effects No other adverse environmental effects (e.g. ozone depletion, photochemical ozone creation

potential, endocrine disruption, global warming potential) are expected from this component.

Material name: 2-26® Multi-Purpose Precision Lubricant

SDS US 02007 Version #: 03 Revision date: 01-07-2016 Issue date: 01-07-2016

13. Disposal considerations

Disposal of waste from residues / unused products

This product is not a RCRA hazardous waste (See 40 CFR Part 261.20 – 261.33). Empty containers may be recycled. Collect and reclaim or dispose in sealed containers at licensed waste disposal site. Do not allow this material to drain into sewers/water supplies. Do not contaminate ponds, waterways or ditches with chemical or used container. Dispose in accordance with all applicable regulations.

Hazardous waste code Not regulated.

Contaminated packaging Since emptied containers may retain product residue, follow label warnings even after container is

emptied. Empty containers should be taken to an approved waste handling site for recycling or

disposal.

14. Transport information

DOT

Not regulated as dangerous goods.

IATA

Not regulated as dangerous goods.

IMDG

Not regulated as dangerous goods.

15. Regulatory information

US federal regulations

All components are on the U.S. EPA TSCA Inventory List.

This product is a "Hazardous Chemical" as defined by the OSHA Hazard Communication

Standard, 29 CFR 1910.1200.

TSCA Section 12(b) Export Notification (40 CFR 707, Subpt. D)

Not regulated.

US. OSHA Specifically Regulated Substances (29 CFR 1910.1001-1050)

Not listed.

SARA 304 Emergency release notification

Not regulated.

US EPCRA (SARA Title III) Section 313 - Toxic Chemical: Listed substance

Not listed.

CERCLA Hazardous Substance List (40 CFR 302.4)

Not listed.

CERCLA Hazardous Substances: Reportable quantity

Not listed.

Spills or releases resulting in the loss of any ingredient at or above its RQ require immediate notification to the National Response Center (800-424-8802) and to your Local Emergency Planning Committee.

Clean Air Act (CAA) Section 112 Hazardous Air Pollutants (HAPs) List

Not regulated.

Clean Air Act (CAA) Section 112(r) Accidental Release Prevention (40 CFR 68.130)

Not regulated.

Safe Drinking Water Act

Not regulated.

(SDWA)

Food and Drug

Not regulated.

Administration (FDA)

Superfund Amendments and Reauthorization Act of 1986 (SARA)

Section 311/312 Immediate Hazard - Yes
Hazard categories Delayed Hazard - No
Fire Hazard - No
Pressure Hazard - No

Pressure Hazard - No Reactivity Hazard - No

SARA 302 Extremely hazardous substance

US state regulations

US. California. Candidate Chemicals List. Safer Consumer Products Regulations (Cal. Code Regs, tit. 22, 69502.3, subd.

(a))

Distillates (petroleum), hydrotreated light (CAS 64742-47-8)

No

Petrolatum (CAS 8009-03-8)

US. Massachusetts RTK - Substance List

Light mineral oil (CAS 8042-47-5)

US. California Controlled Substances. CA Department of Justice (California Health and Safety Code Section 11100)

Not listed.

US. Rhode Island RTK

None.

US. New Jersey Worker and Community Right-to-Know Act

Distillates (petroleum), hydrotreated light (CAS 64742-47-8)

US. Pennsylvania Worker and Community Right-to-Know Law

Distillates (petroleum), hydrotreated light (CAS 64742-47-8)

Light mineral oil (CAS 8042-47-5)

US. California Proposition 65

California Safe Drinking Water and Toxic Enforcement Act of 1986 (Proposition 65): This material is not known to contain any chemicals currently listed as carcinogens or reproductive toxins.

Volatile organic compounds (VOC) regulations

EPA

VOC content (40 CFR

100 %

51.100(s))

Consumer products (40 CFR 59, Subpt. C)

Not regulated

State

Consumer products

This product is regulated as a Multi-Purpose Lubricant. This product is compliant for use in all 50

states.

VOC content (CA) 0 % VOC content (OTC) 0 %

International Inventories

| Country(s) or region | Inventory name | On inventory (yes/no)* |
|----------------------|--|------------------------|
| Australia | Australian Inventory of Chemical Substances (AICS) | Yes |
| Canada | Domestic Substances List (DSL) | No |
| Canada | Non-Domestic Substances List (NDSL) | Yes |
| China | Inventory of Existing Chemical Substances in China (IECSC) | Yes |
| Europe | European Inventory of Existing Commercial Chemical Substances (EINECS) | No |
| Europe | European List of Notified Chemical Substances (ELINCS) | No |
| Japan | Inventory of Existing and New Chemical Substances (ENCS) | No |
| Korea | Existing Chemicals List (ECL) | Yes |
| New Zealand | New Zealand Inventory | No |
| Philippines | Philippine Inventory of Chemicals and Chemical Substances (PICCS) | No |
| | | |

^{*}A "Yes" indicates that all components of this product comply with the inventory requirements administered by the governing country(s)

Toxic Substances Control Act (TSCA) Inventory

16. Other information, including date of preparation or last revision

Issue date01-07-2016Revision date01-07-2016Prepared byAllison Cho

Version # 03

United States & Puerto Rico

Further information CRC # 591B-C
HMIS® ratings Health: 1
Flammability: 1

Physical hazard: 0 Personal protection: B

NFPA ratings Health: 1

Flammability: 1 Instability: 0

Material name: 2-26® Multi-Purpose Precision Lubricant

SDS US

Yes

A "No" indicates that one or more components of the product are not listed or exempt from listing on the inventory administered by the governing country(s).

NFPA ratings



Disclaimer

The information contained in this document applies to this specific material as supplied. It may not be valid for this material if it is used in combination with any other materials. This information is accurate to the best of CRC Industries' knowledge or obtained from sources believed by CRC to be accurate. Before using any product, read all warnings and directions on the label. For further clarification of any information contained on this (M)SDS consult your supervisor, a health & safety professional, or CRC Industries.